

AMENDMENTS TO THE CLAIMS

The following listing of claims will replace all prior versions and listings of claims in the application.

LISTING OF CLAIMS

1. 1. – 24 (Cancelled)

25. (Original) A method of turning a magnet element at an operating point inside the body from an initial direction to a desired final direction by moving a source magnet outside the body, the method comprising the steps of:

determining a series of movements of the source magnet to turn the magnet element to successively align with a series of target directions including at least one intermediate direction between the initial direction and the desired final direction, and the desired final direction, such that the direction of the magnetic element during each movement of the source magnet in the series does not deviate from the plane of the initial direction and the desired final direction by more than a predetermined amount; and implementing the determined movements of the source magnet in series to turn the magnetic element from the initial direction to the final direction through the at least one intermediate direction.

26. (Original) The method according to claim 25 where the step of determining the series of movements comprises:

- (a) selecting an initial series of target directions;
- (b) determining the magnet movements needed to apply a magnetic field to turn the magnetic element to the target directions from their respective prior directions, and testing whether such movement causes the direction of the magnetic element to deviate from the plane of the initial direction and the final desired direction by more than a predetermined amount, and if so, selecting new and/or additional intermediate directions for the series of target directions;
- (c) repeating step (b) until series of target directions and corresponding magnet movements have been determined that do not cause the direction of the magnetic

element to deviate from the plane of the initial target direction by more than a predetermined amount.

27. (Original) A method of turning a magnet element at an operating point inside a patient's body from an initial direction to a desired final direction by moving a source magnet outside the body, the method comprising the steps of:

- (a) providing means for determining and maintaining during a procedure the location and orientation of the magnet element relative to the location and orientation of the external source magnet;
- (b) choosing desired field vectors in the patient frame as a series of angularly spaced vectors which lie in the plane of the initial and final vectors and entering them in a processor;
- (c) entering the position and direction of the vectors into a processor by a means of specifying and displaying the field and communicating with the processor;
- (d) calculating field directions at the operating point in the reference frame of the patient by translating the desired vectors into the reference frame of the magnet;
- (e) transforming each one of the sequence of vectors into the reference frame of the source magnet;
- (f) calculating a surface of constant field strength of desired value in the magnet frame;
- (g) locating each of the field vectors on the appropriate latitude of the surface of constant field strength corresponding to the correct transformed direction of the field vector;
- (h) for each pair of sequential vectors of the total set, calculating the minimum motion of the source magnet required to change the field direction, taking advantage of the azimuthal symmetry of the magnet field; and
- (i) executing the desired step turns by articulating the source magnet.

28. (Original) The method of claim 27 in which the articulation of the source magnet uses coordinated translations and rotations to maintain a turn nearly in a plane.

29. (Original) The method of claim 27 in which the magnet element is attached to a medical device.
30. (Original) The method of claim 29 in which the magnet element is attached to a catheter.
31. (Original) The method of claim 29 in which the magnet element is attached to an endoscope.
32. (Original) The method of claim 29 in which the magnet element is attached to an electrode.
33. (Original) The method of claim 27 in which the magnet element is attached to a guide wire.
34. (Original) The method of claim 27 in which the desired turn of the magnet is in a body lumen in a patient.
35. (Original) The method of claim 27 in which the desired turn of the magnet is in body tissue in a patient.
36. (Original) The method of claim 27 in which exclusion zones are entered into, and remain in the processor as vectors in the patient reference frame and transformed into the magnet frame so the processor can use them in providing the proper requested turns while avoiding interferences.
37. (Original) The method of claim 27 in which calculations of possible vectors with a given angular resolution are made in advance and entered into lookup tables.
38. (Original) The method of claim 27 in which the execution of the step turns is the articulation of a single magnet.
39. (Original) The method of claim 27 in which the spacing of the desired intermediate vectors of a turn is checked in the processor for departure of motion from a plane in the patient frame.
40. (Original) The method of claim 27 in which the calculation and execution of the step turns is the articulation of at least two magnets.
41. (Original) The method of claim 36 in which the exclusion zone includes both the interfering objects or beams in the patient frame and those on the articulated magnet.

42. (Original) The method of claim 27 in which turn limitations of the source magnet, such as those from leads, are included in the turn calculations of the processor.
43. (Original) The method of claim 29 in which the vectors calculated for turns take into account the departure of the magnet element in the patient from a field line which is caused by stiffness of the attached medical device to the magnet element.
44. (Original) The method of claim 27 in which the friction of a medium in which the turn occurs is taken into account.
45. (Original) The method of claim 29 in which a locating system provides information about the location, orientation, and twist of the medical device to which the magnet tip is attached.
46. (Original) The method of claim 45 in which the measured twist of the lumen tip is used to provide a display of the internal view from the medical device lumen, corrected for that twist, to the physician.
47. (Original) The method of claim 29 further comprising imaging through the medical device, and providing an intuitive interface so internal viewing through the medical device can be used to navigate the magnet element.
48. (Original) The method of claim 47 in which the navigation interface includes the ability to rotate about the axis of the lumen for complete inspection of the lumen.
49. (Original) The method of claim 47 in which the navigation includes the ability to rotate about the axis of the lumen to provide treatment at a desired point on the wall of the lumen.
50. (Original) The method of claim 27 in which the locating and orienting means is magnetic.
51. (Original) The method of claim 52 in which during articulation of a source magnet the processor uses information on the magnet element from imaging or a locator to correct for departure of the observed motion from that requested.

52. (Original) A method of navigating a small magnet in a patient using articulation of an external magnet source field, in which the navigation algorithm maintains the field magnitude substantially constant at the position of the small magnet during the navigation.
53. (Original) A method of navigating a small magnet in a patient using articulation of an external magnet source field, in which the navigation algorithm uses the symmetry of the source magnet to achieve solutions which will minimize computer memory and time.
54. (Original) A method of navigating a small magnet in a patient using articulation of an external magnet source field, in which the navigation algorithm uses the symmetry of the source magnet to achieve solutions which will minimize source field magnet articulation time.
55. (Original) A method of navigating a small magnet in a patient using articulation of an external magnet source field, which the navigation algorithm uses corrective feedback to reduce the need for precise characterization of distances and physical parameters while maintaining safe, efficient navigation.
56. (Original) A method of navigating a small magnet in a patient using articulation of an external magnet source field with one translation axis and two rotation axes of the articulator.
57. (Cancelled)
58. (Original) A method of turning a medical device having a magnetically responsive element associated with its distal end, at an operating point within an operating region inside a patient's body from an arbitrary first orientation to an arbitrary second orientation, the method comprising moving at least one source magnet in one direction of translation and two directions of rotation.